



Tec/Spec/07-004
Date Established : 24 July 2007
Date Updated : 30 Aug 2007

TECHNICAL SPECIFICATION

NIPPON EASY WASH

With Teflon™ Surface Protector

- Description : Nippon Easy Wash premium washable paint is a premium acrylic paint specially enhanced with Teflon™ surface protector technology for ultimate washability and resistance to common household stains.
- It is suitable on all interior masonry surfaces and ideal for use in areas with high human traffic such as hallways and living areas.
- Type : Acrylic polymer emulsion paint for interior use
- Colour : As per color card
- Finish : Soft sheen finish
- Features
- Teflon™ enhanced formulation
 - Outstanding washability
 - Excellent stain resistance to common household stains
 - Covers hairline cracks
 - Water-resistant
 - Elegant soft sheen finish
 - Long lasting colours
 - Excellent durability
 - Low odour
 - Fast drying
 - Fungus resistant
 - Alkali resistant
 - Easy application
 - Resistant to blistering and peeling
 - Excellent flow and leveling
 - Excellent coverage and hiding power
 - Resistant to fading and chalking
 - Environmentally friendly - Non-toxic, no lead, mercury and heavy

NIPPON EASY WASH

With Teflon™ Surface Protector

APPLICATION DATA

Method	:	Roller or brush
Theoretical Coverage	:	13 m ² / litre (30 microns DFT)
Dilution	:	No dilution is necessary for best performance
Drying Time	:	Touch Dry – 30 minutes at 30 °C
Overcoating Time	:	2 hours minimum based on normal conditions
Surface Preparation	:	<ul style="list-style-type: none"> • Surface must be clean, dry, stable and free from dust, dirt, oil, grease and other contaminants prior to painting • Treat fungus-growth areas with NIPPON ANTI-FUNGUS SOLUTION. Rinse again with clean water and dry
Cleaning	:	Clean all equipment immediately with clean water
Recommended Painting System	:	<ul style="list-style-type: none"> • 1 coat Vinilex 5101 Water-based Wall Sealer or Vinilex 5170 Oil-based Wall Sealer • 2 coats Nippon Easy Wash

GENERAL INFORMATION

Solid Content	:	Above 50% by weight (Based on white colour)
Specific Gravity	:	1.43 ± 0.03 (Based on white colour)
Packing	:	1 litre and 5 litres
Storage	:	Store in a tightly sealed container in a cool dry place.
Shelf Life	:	Up to 18 months in a tightly sealed container
Precaution	:	Avoid direct contact with sensitive skin. Use appropriate protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries Contacts : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com