



60/02/0002/01

TECHNICAL SPECIFICATION

PYLOX

Description	:	An acrylic modified alkyd nitro-cellulose paint that is specially formulated for decorative and protective purposes. It is suitable for both interior and exterior purposes.
Colour	:	A wide selection of colours, available in metallic, pearl, silver and gold colours.
Finish	:	Gloss
Uses	:	It can be used on: <ul style="list-style-type: none"> • Metal • Timber • Paper surfaces
Features	:	Pylox is a multi purpose quick dry spray paint that is also ozone-friendly (CFC-free) and non-toxic. It can cure extremely fast and provides good adhesion on various surfaces. It also has a good film properties such as hardness and flexibility.

APPLICATION DATA

Theoretical Coverage	:	Wood surface - 0.6 - 1.0 m ² per 400 cc (3 passes per coat) Metal surface - 0.8 - 1.6 m ² per 400 cc (3 passes per coat)
Surface Preparation	:	All surfaces must be clean, dry and free from dirt, grease and moisture. Sand to improve adhesion.
Spray Application	:	Shake can vigorously for at least 30 seconds until metal agitator in the can rattle. When spraying, aim spray head at object. Press lever down keeping can in motion from side to side so that coating is deposited evenly. Spray one coat at a time. Several thin coats are better than one heavy coat.
Drying Time	:	Touch Dry - 3 - 5 mins Hard Dry - 20 - 30 mins at 30 °C
Overcoating Time	:	1 hour in normal conditions.
Cleaning	:	After spraying, turn can upside down pointing spray nozzle into refuse can or old paper and push spray head for approximately 2 seconds to clear paint in valve.

PYLOX

GENERAL INFORMATION

Solid Content	:	20 % – 35% by weight
Specific Gravity	:	1.02 ± 0.03 kg/litre
Supplied Viscosity	:	14-16 sec NK 2 Cup
Flash Point	:	5 °C
Packing	:	400 cc per can
Storage	:	Can should be stored at room temperature (below 40°C) with cap facing down.
Shelf Life	:	Up to 24 months in a tightly sealed container.
Precaution	:	<ul style="list-style-type: none">• Do not puncture or incinerate can.• Do not spray on human body• Contains propellant, therefore keep away from heat, sparks and open flame• Ensure adequate ventilation during use.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries Contacts : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com