



TECHNICAL SPECIFICATION

NIPPON VINYL SILK

Description	:	It is a luxurious emulsion finish that gives a smooth, silky appearance to various types of surfaces to blend with modern & sophisticated interior designs.
Type	:	A modified Veova Emulsion
Colour	:	Standard colours as per colour card including Pastel Shades of Gentle Whites. Special colours on request.
Finish	:	Satin Sheen
Uses	:	Decorative coating for internal cement-rendered surfaces, timber and some primed metals. Examples include: <ul style="list-style-type: none"> • Cement Plaster • Partitions • Fibre Boards • Brickwork • Gypsum • Soft Boards • Wooden Doors • Metal Frames
Features	:	<ul style="list-style-type: none"> • Luxurious finish • Up-to-date range of pleasing and attractive colours • Excellent flow and leveling for a smooth classy finish • High resistance to cement chemicals to prevent discolouration • Algae and fungus-resistant • Completely washable • Easy to apply because of low splattering • Hygienic fragrance

APPLICATION DATA

Method	:	Roller, brush, air and air spray									
Theoretical Coverage	:	9 m ² / litre (based on 40 microns DFT and based on white)									
Dilution	:	Use clean water <table style="margin-left: 20px; border-collapse: collapse;"> <tr> <td style="padding-right: 10px;">Brush</td> <td style="padding-right: 10px;">-</td> <td>10% max</td> </tr> <tr> <td>Roller</td> <td>-</td> <td>10% max</td> </tr> <tr> <td>Air Spray</td> <td>-</td> <td>10 ~ 20%</td> </tr> </table> Dilute to only improve workability	Brush	-	10% max	Roller	-	10% max	Air Spray	-	10 ~ 20%
Brush	-	10% max									
Roller	-	10% max									
Air Spray	-	10 ~ 20%									

NIPPON VINYL SILK

Surface Preparation	: Surface must be clean, dry and stable <u>Suggested Treatment</u>
	(i) <u>Dirt/Powder</u> Clean with damp cloth Mild detergent may be used. For powdery surface, a coat of NIPPON VINILEX 5170 WALL SEALER should be applied.
	(ii) <u>Paint Film</u> Remove unstable old film by scraper.
	(iii) <u>Plaster</u> Remove by chisel, scraper, power grinder etc. Replaster to a stable surface with an approved mortar mixture.
	(iv) <u>Oil/Grease</u> Clean off with mild detergent and a little solvent if necessary. Wash thoroughly to remove all trace.
Drying Time	: Touch Dry - 30 minutes at 30 °C
Overcoating Time	: Minimum 2 hours in normal conditions
Cleaning	: Wash all equipment immediately with clean water.

GENERAL INFORMATION

Solid Content	: 53 ± 2% by weight (based on white)
Specific Gravity	: 1.37 ± 0.03 kg/litre (based on white)
Packing	: 1 litre and 5 litres
Storage	: Store in a tightly sealed container in a cool dry place.
Shelf Life	: Up to 18 months in a tightly sealed container.
Precaution	: Avoid direct contact with sensitive skin. Use appropriate protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries Contacts	: Customer Service 6265 5355 (Main Line) 6264 1603 (Fax) www.nipponpaint.com
---------------------------	---