

TECHNICAL DATA SHEET FOR

ODOUR~LESS ANTI-MOULD CEILING WHITE

DESCRIPTION	: Odour~less Anti-Mould Ceiling White is an environmentally favorable green product formulated with anti-mould properties, giving protection against most species of mould. It is formulated for ceilings especially damp areas such as kitchen, bathroom and area around air-conditioners
TYPE	: Modified Acrylic Emulsion for interior use
COLOUR	: White
FINISH	: Matt
USES	: <ul style="list-style-type: none">• Ideally suited for masonry surfaces, such as cement, plastered walls and fibre boards• Ideal for use on ceiling of hospitals, schools, offices and residential buildings• Good for damp areas such as kitchen and bathroom and area around air-conditioners
FEATURES	: <ul style="list-style-type: none">• Non-toxic, does not contain lead, mercury and heavy metals• Anti-mould properties with a broad spectrum protection against most species of mould• Easy application and touch-up• Minimum roller splatter• Excellent flow and leveling which helps to minimize minor surface imperfections• Excellent coverage and hiding power• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme
APPLICATION DATA	
METHOD	: Roller or brush
THEORETICAL COVERAGE	: Approx 9-10 m ² / litre (30 microns DFT)
DILUTION	: No dilution is necessary for best performance
SURFACE PREPARATION	: Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture :There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application

ODOUR~LESS ANTI-MOULD CEILING WHITE

- **Unstable matter** : Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
- **Contaminants** : Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae** :Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks** :Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME : Surface Dry - 30 minutes at 30°C
Hard Dry - 2 hours at 30°C

OVERCOATING TIME : 2 hours based on normal conditions

RECOMMENDED PAINTING SYSTEM : 1 coat of 5101 Odour-less Sealer
2 coats of Odour~less Anti-Mould Ceiling White

CLEANING : All equipment should be cleaned with water immediately after use

GENERAL INFORMATION

SOLID CONTENT : 48 ± 2% by weight

SPECIFIC GRAVITY : 1.38 ± 2% kg/litre

PACKING : 5 litres

STORAGE : Store in a tightly sealed container in a cool dry place

SHELF LIFE : Up to 24 months in a tightly sealed container

PRECAUTION : Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment
Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg