

TECHNICAL DATA SHEET FOR

AQUA ANTI-STICK ENHANCER CLEAR

DESCRIPTION	:	Aqua Anti-Stick Enhancer Clear is a water-based clear top coat developed specially for Aqua Enamel Anti-Stick paint to provide an enhancement to the anti-stick property
TYPE	:	Water-based clear coat with special anti-stick property for interior and exterior use
COLOUR	:	Clear, pale yellowish
FINISH	:	Low sheen finish
USES	:	As a topcoat over Aqua Enamel Anti-Stick paint only
FEATURES	:	<ul style="list-style-type: none">• Providing enhanced anti-stick ability to Aqua Enamel Anti-Stick paint to resist liquid glue, glue stick, double-sided tape, scotch tape and masking tape• Resistance to fungus and algae• Low odour and environmentally friendly

APPLICATION DATA

METHOD	:	Brush or roller
THEORETICAL COVERAGE	:	Approx. 15 – 20 m ² / litre
DILUTION	:	Ready for use, no dilution required
SURFACE PREPARATION	:	<ul style="list-style-type: none">• Surface must be clean, dry and free from grease, wax and polishes• Clean off fungi and algae and if necessary, treat with Anti-Fungus Solution• Do not apply over bare substrates, wood varnish, shellac and lacquers
DRYING TIME	:	Surface dry - 30 minutes at 30 °C Hard dry - 2 hours at 30 °C
OVERCOATING TIME	:	2 – 4 hours under normal conditions
RECOMMENDED PAINTING SYSTEM	:	2 coats of Aqua Enamel Anti-Stick 1 coat of Aqua Anti-Stick Enhance Clear
CLEANING	:	All equipments should be cleaned with water immediately after use

AQUA ANTI-STICK ENHANCER CLEAR**GENERAL INFORMATION**

- SOLID CONTENT** : 8.0 ± 2.0 % by weight
- SPECIFIC GRAVITY** : 1.0 ± 2.0 % kg / litre
- PACKING** : 5 litres
- STORAGE** : Store in a tightly sealed container in a cool, dry place
- SHELF LIFE** : Up to 12 months in a tightly sealed container
- PRECAUTION** : Avoid painting when the temperature is below 10 °C or 35 °C or when the humidity is over 85 %. This product is flammable. Ensure adequate protection and avoid direct contact on sensitive skin, eye, etc. Use appropriate personal protective equipment

Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg