

## TECHNICAL DATA SHEET FOR

**DURASIL**

<b>DESCRIPTION</b>	:	Durasil is a water-based coating system formulated with high premium silicone dispersion that provides excellent UV resistance and durability. Durasil offers low water absorption and high water vapour transmissions which promote the breathability of the coating
<b>TYPE</b>	:	Water-based Silicone Emulsion Paint
<b>COLOUR</b>	:	As per colour card
<b>FINISH</b>	:	Matt
<b>USES</b>	:	A premium coating for protection of external masonry surfaces
<b>FEATURES</b>	:	<ul style="list-style-type: none"><li>• Excellent water repellency</li><li>• Excellent breathability</li><li>• Long lasting colours</li><li>• Excellent dirt pick-up resistance against industrial air pollution</li><li>• Non-toxic, does not contain lead, mercury and heavy metals</li><li>• Anti-fungus and anti-algal properties</li><li>• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme</li></ul>

**APPLICATION DATA**

<b>METHOD</b>	:	Roller or brush
<b>THEORETICAL COVERAGE</b>	:	8.0 m <sup>2</sup> /litre (based on 40 microns DFT and based on white)
<b>DILUTION</b>	:	Not recommended for best performance
<b>SURFACE PREPARATION</b>	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none"><li>• <b>Moisture</b> :There must not be any water residue on the surface of the substrate. Moisture must be &lt;4% (Sovereign moisture master) before application</li><li>• <b>Unstable matter</b> :Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable</li><li>• <b>Contaminants</b> :Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry</li></ul>

**DURASIL**

<b>SURFACE PREPARATION</b>	:	<ul style="list-style-type: none"><li>• <b>Fungus and Algae</b> :Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours</li><li>• <b>Hairline cracks</b> : Fill cracks with suitable exterior grade water-resistant putty or filler</li></ul>
<b>DRYING TIME</b>	:	Touch Dry - 1 hour at 30 °C
<b>OVERCOATING TIME</b>	:	4 hours based on normal conditions
<b>RECOMMENDED PAINTING SYSTEM</b>	:	<b><u>New Surfaces:</u></b> <ul style="list-style-type: none"><li>• 1 coat Watershield W350</li><li>• 2 coats Durasil</li></ul> <b><u>Old Surfaces:</u></b> <ul style="list-style-type: none"><li>• 1 coat Vinilex 2000 Water-Based Wall Sealer</li><li>• 2 coats Durasil</li></ul>
<b>CLEANING</b>	:	Wash all equipment immediately with clean water after use.
<b>GENERAL INFORMATION</b>		
<b>SOLID CONTENT</b>	:	53 ± 2% by weight (Based on White)
<b>SPECIFIC GRAVITY</b>	:	1.42 ± 2% kg/litre (Based on white)
<b>PACKING</b>	:	20 litres
<b>STORAGE</b>	:	Store in a tightly sealed container in a cool dry place.
<b>SHELF LIFE</b>	:	Up to 24 months when stored in a tightly sealed container.
<b>PRECAUTION</b>	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

**Enquiries / Contact Details** : **Customer Service**  
**6265 5355 (Main Line)**  
**6264 1603 (Fax)**  
**[www.nipponpaint.com.sg](http://www.nipponpaint.com.sg)**