

TECHNICAL DATA SHEET FOR

ECO INTERIOR WALL SEALER

DESCRIPTION	:	ECO Interior Wall Sealer is a water-based, environmentally favorable GREEN product with low VOCs (Volatile Organic Compound) and low odour during application and drying. It is formulated for use on most interior masonry surface to resist alkali attack and provides good hiding coat for emulsion finishing.
TYPE	:	Modified Acrylic Emulsion for interior use
COLOUR	:	White
FINISH	:	Matt
USES	:	As a sealer for interior masonry surfaces such as: <ul style="list-style-type: none">• Concrete / Cement• Fibre-Cement panels• Partition panels / Plasterboard
FEATURES	:	<ul style="list-style-type: none">• Low odour• Good adhesion and alkaline resistance• Anti-fungus property• Fast drying time• Easy application• Non-toxic. Does not contain heavy metals• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme

APPLICATION DATA

METHOD	:	Roller or brush
THEORETICAL COVERAGE	:	Approx 10-12 m ² / litre (30 microns DFT)
DILUTION	:	No dilution is necessary for best performance
SURFACE PREPARATION	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture :There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application• Unstable matter :Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable

ECO INTERIOR WALL SEALER

- **Contaminants** :Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae** :Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks** :Fill cracks with suitable exterior grade water-resistant putty or filler

DRYING TIME : Surface Dry - 30 minutes at 30 °C
Hard Dry - 1 hour at 30 °C

OVERCOATING TIME : 2 hours based on normal conditions

RECOMMENDED PAINTING SYSTEM : 1 coat of ECO Interior Wall Sealer
2 coats of Finishing top coat

CLEANING : All equipment should be cleaned with water immediately after use.

GENERAL INFORMATION

SOLID CONTENT : 57 ± 2% by weight

SPECIFIC GRAVITY : 1.31 ± 2% kg/litre

PACKING : 20 litres

STORAGE : Store in a tightly sealed container in a cool dry place.

SHELF LIFE : Up to 24 months in a tightly sealed container.

PRECAUTION : Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment.
Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg