



SAFETY DATA SHEET

SDS Number: SDS/OTH-0071

Version No: 002

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: **FLOOR-PRO 109 SB EPOXY PRIMER PART A**
Intended Use: Solvent-Based Floor Coating
Supplier/Manufacturer: Nippon Paint (S) Co. Pte Ltd
No. 1 First Lok Yang Road
Jurong Singapore 629728
Emergency Phone Number: (65) 6 265 5355
Fax Numbers: (65) 6 264 1603

2. HAZARDS IDENTIFICATION

GHS Classification:

Physical Hazard

Flammable Hazard Category 2

Health Hazard

Serious eye damage/irritation Category 2
Skin sensitization Category 1
Reproductive toxicity Category 2
Specific target organ toxicity
-Single exposure Category 3
- Repeated exposure Category 2
Aspiration toxicity Category 1

Environment Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Danger

Hazard statements

H225 Highly flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H361 Suspected of damaging fertility or the unborn child
H373 May cause damage to organs through prolonged or repeated exposure

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood
P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking

- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ventilating/light/equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P260 Do not breathe dust/fume/gas/mist/vapours/spray
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray
- P264 Wash hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P281 Use personal protective equipment as required
- P321 Specific treatment (see Section 4 of SDS)
- P362 Take off contaminated clothing and wash before reuse

Response

- P312 Call a POISON CENTER or doctor/physician if you feel unwell
- P314 Get Medical advice/attention if you feel unwell
- P321 Specific treatment (see Section 4 of SDS)
- P331 Do NOT induce vomiting
- P363 Wash contaminated clothing before reuse
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P302+352 IF ON SKIN: Wash with soap and water
- P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P308+313 IF exposed or concerned: Get medical advice/attention
- P332+313 If skin irritation occurs: Get medical advice/attention
- P333+313 If skin irritation or a rash occurs: Get medical advice/attention
- P337+313 If eye irritation persists: Get medical advice/attention
- P370+378 In case of fire: Use appropriate media for extinction
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage

- P405 Store locked up
- P403+233 Store in a well ventilated place. Keep container tightly closed
- P403+235 Store in a well ventilated place. Keep cool

Disposal

- P501 Dispose of content/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS No.</u>	<u>%</u>
Bisphenol-A-type Epoxy Resin	25036-25-3	80
Toluene	108-88-3	10
Isopropyl Alcohol	67-63-0	8

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens
- Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

- DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol-resistant foam, Carbon dioxide, or dry chemical type

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.
- Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow run-off from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.
- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.

- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well-ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

<u>Ingredient</u>	<u>ACGIH TLV-TWA</u>		<u>OSHA PEL-TWA</u>	
	<u>ppm</u>	<u>mg/m3</u>	<u>ppm</u>	<u>mg/m3</u>
Bisphenol-A-type Epoxy Resin	-	-	-	-
Toluene	-	188.00	-	-
Isopropyl Alcohol	-	-	-	-

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

Respiratory Protection: Use of NIOSH-approved respirators with organic vapour cartridges is recommended.

Hand Protection: Use of solvent resistance type or chemical resistant type of protective gloves is recommended.

Eye Protection: Use of safety glasses or goggles with side shields is recommended.

Skin / Body Protection: Wear chemical resistant clothes and safety shoes when handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid
Odour	:	Aromatic hydrocarbon odour
Odour threshold	:	Not available
pH	:	Not available
Melting point/freezing point	:	Not available
Initial boiling point and boiling range	:	Between 82 and 137 degC
Flash point	:	7 degC
Evaporation rate	:	Not available
Flammability (solid, gas)	:	Not applicable
Lower flammability or explosive limit	:	Not available
Upper flammability or explosive limit	:	Not available
Vapour pressure	:	Not available
Vapour density	:	> 1.00 (Vapour is heavier than air)
Relative density	:	Not available
Solubility	:	Not Miscible in water
Partition coefficient	:	Not available
Auto-ignition temperature	:	Not available

Decomposition temperature : Not available
Viscosity : Not available

10. STABILITY AND REACTIVITY

REACTIVITY

- No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

- The product is stable under recommended storage and handling conditions. (see section 7)

POSSIBILITY OF HAZARDOUS REACTION

- Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

- Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

- When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.
Toxicological information of ingredients:

Acute Oral toxicity

Harmful if swallowed.

<u>Ingredient</u>	<u>Oral LD50(Rat), mg/kg</u>
Bisphenol-A-type Epoxy	Data not available
Toluene	5580
Isopropyl Alcohol	Data not available

Acute dermal/skin toxicity

<u>Ingredient</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
Bisphenol-A-type Epoxy	Data not available
Toluene	12196
Isopropyl Alcohol	Data not available

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

<u>Ingredient</u>	<u>Inhalation Vapor LC50 (Rat), mg/L/4hr</u>
Bisphenol-A-type Epoxy	Data not available
Toluene	28800
Isopropyl Alcohol	Data not available

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant.

Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract,

Germ cell mutagenicity

No information available on the product.

Carcinogenicity

No information available on the product.

Reproductive toxicity

No information available on the product.

Specific Target Organ Toxicity (STOT)- single exposure

No information available on the product.

Specific Target Organ Toxicity (STOT)- repeated exposure

No information available on the product.

Aspiration hazard

May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

Toxicity

-No data available

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

-No data available

Mobility in soil

-No data available

Result of PBT and vPvB assessment

-No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.
The product should not be allowed to enter drains or water courses

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.

Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: 1263
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 1263
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II
Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number: 1263
Proper Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586 : Part 1: 2014- Transport and storage of dangerous goods
 - SS 586 : Part 2: 2014- GHS of classification and labelling of chemicals- Singapore's adaptations
 - SS 586 : Part 3: 2008- Preparation of safety data sheets (SDS)
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations.
 - This product is not subject to control under this Acts/Regulations
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations

- This product is subject to the requirement of this Acts/Regulations
 - SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations
-

16. OTHER INFORMATION

Revision date: 01-Apr-2019

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.



SAFETY DATA SHEET

SDS Number: SDS/OTH-0072

Version No: 002

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Name: **FLOOR-PRO 109 SB EPOXY PRIMER PART B**
Intended Use: Solvent-Based Floor Coating
Supplier/Manufacturer: Nippon Paint (S) Co. Pte Ltd
No. 1 First Lok Yang Road
Jurong Singapore 629728
Emergency Phone Number: (65) 6 265 5355
Fax Numbers: (65) 6 264 1603

2. HAZARDS IDENTIFICATION

GHS Classification:

Physical Hazard

Flammable Hazard Category 2

Health Hazard

Acute Toxicity:
- Inhalation Category 4
Skin corrosion/Irritation Category 1
Serious eye damage/irritation Category 2
Skin sensitization Category 1
Reproductive toxicity Category 2
Specific target organ toxicity
-Single exposure Category 3
- Repeated exposure Category 2
Aspiration toxicity Category 1

Environment Hazard

Not classified as an environmental hazard under GHS criteria

GHS Pictogram



Signal Word

Danger

Hazard statements

H225 Highly flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H314 Causes severe skin burns and eye damage
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

Precautionary statements

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ventilating/light/equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P260 Do not breathe dust/fume/gas/mist/vapours/spray
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray
- P363 Wash contaminated clothing before reuse
- P264 Wash hands thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P281 Use personal protective equipment as required

Response

- P310 Immediately call a POISON CENTER or doctor/physician
- P312 Call a POISON CENTER or doctor/physician if you feel unwell
- P314 Get Medical advice/attention if you feel unwell
- P321 Specific treatment (see Section 4 of SDS)
- P331 Do not induce vomiting
- P362 Take off contaminated clothing and wash before reuse
- P363 Wash contaminated clothing before reuse
- P301+310 IF SWALLOWED Immediately call a POISON CENTER or doctor/physician
- P302+352 IF ON SKIN Wash with soap and water
- P304+340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P308+313 IF exposed or concerned Get medical advice/attention
- P333+313 If skin irritation or a rash occurs Get medical advice/attention
- P337+313 If eye irritation persists Get medical advice/attention
- P370+378 In case of fire: Use appropriate media for extinction
- P303+361+353 IF ON SKIN (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P305+351+338 IF IN EYES Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage

- P405 Store locked up
- P403+233 Store in a well ventilated place. Keep container tightly closed
- P403+235 Store in a well ventilated place. Keep cool

Disposal

- P501 Dispose of content/container to appropriate waste site or reclaimer in accordance with local or national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS No.	%
Methyl Isobutyl Ketone	108-10-1	5
Toluene	108-88-3	49
Isopropyl Alcohol	67-63-0	12
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	4
Bis(dimethylamino)methyl)Phenol	71074-89-0	2

4. FIRST-AID MEASURES

INHALATION

- Move person to fresh air and call for medical assistance immediately.
- If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Keep at rest.

SKIN CONTACT

- In case of contact, immediately flush skin with large amounts of water and soap while removing contaminated clothing and shoes.
- If irritation persists, get medical attention.

EYE CONTACT

- Immediately flush eyes with large amounts of water until irritation subsides.
- Remove contact lens
- Obtain medical attention, preferably by an ophthalmologist, immediately.

INGESTION

- DO NOT induce vomiting unless directed to do so by a medical personnel. Never give anything by mouth to an unconscious person. Keep at rest. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

SUITABLE FIRE EXTINGUISHING MEDIA

- Alcohol-resistant foam, Carbon dioxide, or dry chemical type

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Combustion products may include and are not limited to: Carbon monoxide and Carbon dioxide.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

- Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.
- Use water spray to cool fire-exposed surfaces and to protect personnel. If a leak or spill has not ignited, use water spray to disperse the vapours.
- If possible, isolate product from heat, electrical equipments, sparks and open flames.
- Avoid spraying water directly into storage containers.
- Closed containers may explode when exposed to extreme heat.
- Avoid spreading burning liquid with water, isolate liquid.
- Do not allow run-off from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

- Wear appropriate protective equipment, e.g. respirators, eye protection, gloves and safety shoes.
- Avoid substance contact with eyes. Do not inhale vapours.
- Ensure supply of fresh air in enclosed rooms.

ENVIRONMENTAL PRECAUTIONS

- Eliminate sources of ignition.
- Keep public away.
- Contain spilled liquid with sand or other non-combustible absorbent materials
- Wash area and prevent runoff into drains and sewerage system.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEANING UP

- Clean up all spills immediately.
- Absorb spill with absorbent and inert material, then place in container.

- Disposal in accordance to local/national regulations.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Use appropriate personal protective equipment
- Keep out of reach of children.
- Handle containers with care. Open slowly in order to control possible pressure release.
- Do not pressurize containers.
- Do not ingest. Do not breathe in gas/fumes/vapour. Avoid contact with skin and eyes.
- For personal protection, see section 8.
- Use only in areas from which all naked lights and other sources of ignition have been excluded.
- Take precautionary measures against static discharge
- Protect from frost and extremes of temperature.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Keep containers tightly closed.
- Containers that are opened should be properly resealed and kept upright to prevent leakage.
- Store in cool, dry and well-ventilated place at temperature between 20°C to 40°C away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS/OCCUPATIONAL LIMITS

Ingredient	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m³	ppm	mg/m³
Methyl Isobutyl Ketone	50	-	-	-
Toluene	-	188.00	-	-
Isopropyl Alcohol	-	-	-	-
2,4,6-tris(dimethylaminomethyl)phenol	-	-	-	-
Bis(dimethylamino)methyl)Phenol	-	-	-	-

APPROPRIATE ENGINEERING CONTROL MEASURES

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
- Ensure eyewash stations and safety showers are close to the workstation location.

PERSONAL PROTECTION

Respiratory Protection:	Use of NIOSH-approved respirators with organic vapour cartridges is recommended.
Hand Protection:	Use of solvent resistance type or chemical resistant type of protective gloves is recommended.
Eye Protection:	Use of safety glasses or goggles with side shields is recommended.
Skin / Body Protection:	Wear chemical resistant clothes and safety shoes when handling product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid
Odour	:	Aromatic hydrocarbon odour
Odour threshold	:	Not available
pH	:	Not available
Melting point/freezing point	:	Not available
Initial boiling point and boiling range	:	Between 111 and 277 degC
Flash point	:	7 degC
Evaporation rate	:	Not available

Flammability (solid, gas)	:	Not applicable
Lower flammability or explosive limit	:	Not available
Upper flammability or explosive limit	:	Not available
Vapour pressure	:	Not available
Vapour density	:	> 1.00 (Vapour is heavier than air)
Relative density	:	Not available
Solubility	:	Not Miscible in water
Partition coefficient	:	Not available
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
Viscosity	:	Not available

10. STABILITY AND REACTIVITY

REACTIVITY

- No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

- The product is stable under recommended storage and handling conditions. (see section 7)

POSSIBILITY OF HAZARDOUS REACTION

- Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

- Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, drill, grind or expose containers to heat or sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS

- When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Toxicological information of ingredients:

Acute Oral toxicity

Harmful if swallowed.

<u>Ingredient</u>	<u>Oral LD50(Rat), mg/kg</u>
Methyl Isobutyl Ketone	2080
Toluene	5580
Isopropyl Alcohol	Data not available
2,4,6-tris(dimethylaminomethyl)phenol	Data not available
Bis(dimethylamino)methyl)Phenol	Data not available

Acute dermal/skin toxicity

<u>Ingredient</u>	<u>Dermal LD50 (Rabbit), mg/kg</u>
Methyl Isobutyl Ketone	1600
Toluene	12196
Isopropyl Alcohol	Data not available
2,4,6-tris(dimethylaminomethyl)phenol	Data not available
Bis(dimethylamino)methyl)Phenol	Data not available

Acute inhalation toxicity

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects.

<u>Ingredient</u>	<u>Inhalation Vapor LC50 (Rat), mg/L/4hr</u>
Methyl Isobutyl Ketone	16.4
Toluene	28800
2,4,6-tris(dimethylaminomethyl)phenol	Data not available
Bis(dimethylamino)methyl)Phenol	Data not available

Skin corrosion or irritation

Causes skin irritation. Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Serious eye damage or irritation

May be an eye irritant.

Respiratory or skin sensitisation

Vapour concentrations above the recommended exposure levels may be irritating to the eyes and the respiratory tract,

Germ cell mutagenicity

No information available on the product.

Carcinogenicity

No information available on the product.

Reproductive toxicity

No information available on the product.

Specific Target Organ Toxicity (STOT)- single exposure

No information available on the product.

Specific Target Organ Toxicity (STOT)- repeated exposure

No information available on the product.

Aspiration hazard

May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

Toxicity

-No data available

Persistence and degradability

Biodegradation -No data available

Bioaccumulative potential

-No data available

Mobility in soil

-No data available

Result of PBT and vPvB assessment

-No data available

Other adverse effects

There is no ecotoxicological test data available on the product itself.
The product should not be allowed to enter drains or water courses

13. DISPOSAL CONSIDERATIONS

The product should not be allowed to enter drains and watercourses.

Preferred methods of waste disposal are incineration or biological treatment in federal/state approved facility. Empty containers should be recycled or disposed through an approved waste management facility or licensed contractor.

All federal, state and local environmental regulations shall be observed.

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number: 1263
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number: 1263
Proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II
Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number: 1263
Proper Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).
Class: Class 3
Packaging Group: II

15. REGULATORY INFORMATION

Applicable national regulations:

- Standards on Hazard communication for hazardous chemicals and dangerous goods
 - SS 586 : Part 1: 2014- Transport and storage of dangerous goods
 - SS 586 : Part 2: 2014- GHS of classification and labelling of chemicals- Singapore's adaptations
 - SS 586 : Part 3: 2008- Preparation of safety data sheets (SDS)
- MOM: Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
 - This product is subject to SDS, labelling, PEL and other requirements in the Acts/Regulations
- NEA: Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations.
 - This product is not subject to control under this Acts/Regulations
- SCDF: Fire Safety Act & Fire Safety (Petroleum and Flammable Materials) Regulations
 - This product is subject to the requirement of this Acts/Regulations
- SPF: The Arms and Explosive Act, the Arms and Explosives (Explosives) Rules, and the Arms and Explosives (Explosive Precursors) Rules
 - This product is not subject to the requirement of this Acts/Regulations

16. OTHER INFORMATION

Revision date: 01-Apr-2019

Abbreviation

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IARC International Agency for Research in Cancer

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.