

## TECHNICAL DATA SHEET FOR

**STONE ART CLEAR GLOSS**

<b>DESCRIPTION</b>	:	Stone Art Clear Gloss is a single component water-based modified acrylic emulsion designed for exterior and interior clear topcoat for Stone Art multi colour coatings.
<b>TYPE</b>	:	Water-based acrylic emulsion topcoat
<b>COLOUR</b>	:	Clear
<b>FINISH</b>	:	Gloss finish
<b>USES</b>	:	<ul style="list-style-type: none"><li>• Recommended on new and old surfaces coated with multi colour texture coats.</li></ul>
<b>FEATURES</b>	:	<ul style="list-style-type: none"><li>• Protects the multi colour texture against harsh climate conditions</li><li>• Fungus and algae resistance</li><li>• Water whitening resistant</li><li>• Environmentally friendly</li><li>• Excellent colour stability (non-yellowing)</li><li>• Excellent adhesion and bonding strength</li><li>• Excellent workability and application</li></ul>
<b>APPLICATION DATA</b>		
<b>METHOD</b>	:	Roller or Spray
<b>THEORETICAL COVERAGE</b>	:	10 – 15m <sup>2</sup> / ltr (will vary due to factors such as application method and conditions, surface profile and absorption and etc)
<b>DILUTION</b>	:	Ready to use.
<b>DESCRIPTION</b>	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none"><li>• <b>Moisture:</b> There must not be any water residue on the surface of the substrate. Moisture must be &lt;4% (Sovereign moisture master) before application</li><li>• <b>Unstable matter:</b> Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable</li></ul>

## STONE ART CLEAR GLOSS

- **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks :** Fill cracks with suitable exterior grade water-resistant putty or filler

**DRYING TIME** : Surface Dry - 30 mins @30°C  
Hard dry - 1 hour @30°C

**OVERCOATING TIME** : 2 hours

**RECOMMENDED PAINTING SYSTEM** :

- 1 coat Vinilex 2000 Water-based Wall Sealer
- 1 coat Stone Art Texture
- 2 coat Stone Art
- 1 coat Stone Art Clear Gloss

**CLEANING** : All equipments should be cleaned with water immediately after use

### GENERAL INFORMATION

**SOLID CONTENT** : 25.0 ± 5.0 % by weight

**SPECIFIC GRAVITY** : 1.10 ± 2.0 % kg / litre

**PACKING** : 5 ltr / can

**STORAGE** : Store in a tightly sealed container in a cool dry place, away from heat source or ignition.

**SHELF LIFE** : Up to 6 months in a tightly sealed container in a cool dry place.

**PRECAUTION** : Ensure good ventilation during application and drying of paint. Do not apply in air and substrate temperature below 5°C. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment

Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

**Enquiries / Contact Details** : **Customer Service**  
6265 5355 (Main Line)  
6264 1603 (Fax)  
[www.nipponpaint.com.sg](http://www.nipponpaint.com.sg)