

**TECHNICAL DATA SHEET FOR  
STONE ART TEXTURE**

- DESCRIPTION** : Stone Art Texture is a premium decorative sand texture coating. It is especially designed for Stone Art stereographic effect. It consists of various sizes of aggregates bound by water-based weather resistant modified acrylic binder suitable for external and internal masonry and other building surfaces.
- TYPE** : Aggregates in water-based acrylic polymer
- COLOUR** : White
- FINISH** : Matt finish
- USES** :
  - Suitable for primed concrete, plaster, brickworks, soft boards, hard boards, timber and gypsum surfaces, but must be painted over with appropriate finishing paint for weather resistance and other function properties.
- FEATURES** :
  - Creates a sandstone-like effect
  - Good durability and weatherability
  - Available in any customized patterns and design
  - Semi-flexible and breathable
  - Environmentally friendly
  - Available in any customized patterns and design
- APPLICATION DATA**
- METHOD** : Spray
- THEORETICAL COVERAGE** : 0.5 – 1.0m<sup>2</sup> / kg  
(depend on texture size and density of spray and will vary due to factors such as application method and conditions, surface profile and absorption and etc)
- DILUTION** : Ready to use. If thinning is required, add not more than 5% clean water
- DESCRIPTION** : Ensure surface is clean, dry and stable using the following suggested surface treatments:
- **Moisture:** There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application
  - **Unstable matter:** Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable

- **Contaminants:** Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae:** Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks:** Fill cracks with suitable exterior grade water-resistant putty or filler

**DRYING TIME** : Surface Dry - 2 hours @ 30°C  
Hard dry - 24 hours @ 30°C

**OVERCOATING TIME** : 24 hours for topcoating

**RECOMMENDED PAINTING SYSTEM** :

- 1 coat Vinilex 2000 Water-based Wall Sealer
- 1 coat Stone Art Texture
- 2 coat Stone Art
- 1 coat Stone Art Clear Gloss

**CLEANING** : All equipments should be cleaned with water immediately after use

### **GENERAL INFORMATION**

**SOLID CONTENT** : 85.0 ± 5.0 % by weight

**SPECIFIC GRAVITY** : 1.80 ± 2.0 % kg / litre

**PACKING** : 20 Kg / can

**STORAGE** : Store in a tightly sealed container in a cool dry place, away from heat source or ignition.

**SHELF LIFE** : Up to 6 months in a tightly sealed container in a cool dry place.

**PRECAUTION** : Ensure good ventilation during application and drying of paint. Do not apply in air and substrate temperature below 5°C. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment

Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

**Enquiries / Contact Details** : **Customer Service**  
**6265 5355 (Main Line)**  
**6264 1603 (Fax)**  
**[www.nipponpaint.com.sg](http://www.nipponpaint.com.sg)**