

## TECHNICAL DATA SHEET FOR

**BODELAC 9000 ALUMINIUM WOOD PRIMER**

<b>DESCRIPTION</b>	:	Oil-modified Phenolic vehicle with aluminium pigment as its primary pigment. SISIR Approved Product
<b>TYPE</b>	:	Oil-modified Phenolic
<b>COLOUR</b>	:	Aluminium
<b>FINISH</b>	:	Semi-Gloss
<b>USES</b>	:	<p>Primer for wooden surfaces. Its excellent sealing property makes it an efficient sealer for woodwork both internally &amp; externally. Application surfaces include:</p> <ul style="list-style-type: none"><li>• Timber floors</li><li>• Timber-top work benches</li><li>• Furniture</li><li>• Doors</li></ul>
<b>FEATURES</b>	:	<ul style="list-style-type: none"><li>• Effective sealing ability</li><li>• Excellent adhesion on wooden substrates</li><li>• High spreading rate</li><li>• Faster-drying than most similar primers</li><li>• Economical and easy to use</li></ul>
<b>APPLICATION DATA</b>		
<b>METHOD</b>	:	Roller, brush or air spray
<b>THEORETICAL COVERAGE</b>	:	16.7m <sup>2</sup> / litre (30 µ DFT)
<b>DILUTION</b>	:	<p>Use Bodelac 9000 GP Thinner Roller – 10% max Brush - 10% max Air spray - 10 ~ 20% Thin only to improve workability</p>
<b>SURFACE PREPARATION</b>	:	<p>Ensure that wood is:</p> <ul style="list-style-type: none"><li>• Dry (Moisture not more than 12%)</li><li>• Sand to smooth surface</li><li>• Sand previous coat (repainting)</li><li>• Clean/Dry</li><li>• Stable</li><li>• Free of oil/grease</li></ul>

**BODELAC 9000 ALUMINIUM WOOD PRIMER**

<b>DRYING TIME</b>	:	Touch Dry – 1½ hours at 30°C
<b>OVERCOATING TIME</b>	:	Minimum 14 hrs
<b>RECOMMENDED PAINTING SYSTEM</b>	:	<ul style="list-style-type: none"><li>• 1 coat of Bodelac 9000 Aluminium Wood Primer</li><li>• 2 coats of suitable top coat</li></ul>
<b>CLEANING</b>	:	All equipment should be cleaned with Bodelac 9000 GP Reducer immediately after use
<b>GENERAL INFORMATION</b>		
<b>SOLID CONTENT</b>	:	50± 2% by weight
<b>SPECIFIC GRAVITY</b>	:	0.95 ± 2% kg / litre
<b>PACKING</b>	:	5 litres
<b>STORAGE</b>	:	Store in a tightly sealed container in a cool dry place
<b>SHELF LIFE</b>	:	Up to 24 months in a tightly sealed container
<b>PRECAUTION</b>	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

<b>Enquiries / Contact Details</b>	:	<b>Customer Service</b> <b>6265 5355 (Main Line)</b> <b>6264 1603 (Fax)</b> <b><a href="http://www.nipponpaint.com.sg">www.nipponpaint.com.sg</a></b>
------------------------------------	---	--